

SELBSTANSAUGENDE SCHMUTZWASSERPUMPEN

LEISTUNGEN

Pumpentyp	Anschluss [Zoll]	[mm]	Feststoff - Ø [mm]	Q [m³/h]	H [m]	Motorstärke [kW]	Laufzeit [min]	Lagerbock- Größe
2.900 1/min								
S 40	1 1/4"	40	20	20 / 25 / 12	5 / 11 / 15	1	110	1
S 45	1 1/2"	40	15	20 / 25 / 12	11 / 23 / 30	2	172	2
S 50	2"	50	25	40 / 25 / 12	5 / 10 / 16	2	120	2
S 60	2"	50	17	40 / 25 / 12	12 / 23 / 30	4	172	3
S 63	2"	50	15	40 / 25 / 12	16 / 28 / 40	8	195	3
S 68	2"	50	25	40 / 25 / 12	34 / 48 / 57	11	220	4
S 80	3"	80	30	80 / 50 / 30	6 / 14 / 18	4	140	3
S 83	3"	80	20	80 / 50 / 30	11 / 22 / 30	8	172	3
S 88	3"	80	30	80 / 50 / 30	34 / 48 / 53	15	220	4
S 100	4"	100	45	150 / 100 / 50	7 / 19 / 26	11	160	4
S 108	4"	100	40	140 / 100 / 50	20 / 37 / 47	22	220	5
1.450 1/min								
S 65	2"	50	25	40 / 25 / 12	5 / 11 / 14	2	220	4
S 85	3"	80	40	80 / 50 / 30	6 / 12 / 14	4	220	4
S 105	4"	100	45	150 / 100 / 50	4 / 10 / 13	6	220	4
S 120	4"	100	45	150 / 100 / 50	8 / 16 / 22	11	280	5
S 150	6"	150	60	300 / 200 / 100	4 / 10 / 12	11	220	5
S 160	6"	150	60	300 / 200 / 100	8 / 16 / 22	19	280	5
S 180	6"	150	45	300 / 200 / 100	18 / 29 / 34	30	358	6
S 200	8"	200	57	500 / 350 / 200	4 / 12 / 17	22	280	6
S 230	8"	200	72	500 / 350 / 200	16 / 26 / 33	55	358	6
960 1/min								
S 170	6"	150	50	300 / 200 / 100	4 / 11 / 15	11	358	6
S 220	8"	200	80	500 / 350 / 200	4 / 8 / 12	19	358	6
S 300	12"	300	70	1.400 / 1.000 / 500	4 / 10 / 13	55	405	7