

Prestaties

AL 20
AL 25
AL 40
AL 50



Art.	Serie Series Série	Bocche Hoses Orifices	Adescamento Priming Amorçage(m)	Giri/min. max Max r.p.m. Tours/min. max
740	AL 20	3/4" M	6	2900
741	AL 25	1" M	6	2900
744	AL 40	1"1/2 M	6	2400
745	AL 50	2" M	6	1800

Art.	Serie Series Série	PORTATA - CAPACITY - DEBIT (LT./MIN.)										
		1400 giri/min. 1400 r.p.m. 1400 tours/min.			1900 giri/min. 1900 r.p.m. 1900 tours/min			2800 giri/min. 2800 r.p.m. 2800 tours/min.				
		H (m)	1	5	10	1	5	10	1	10	20	30
740	AL 20	Q	11			18	9		28	17	5	
		HP	0.1			0.1	0.1		0.2	0.2	0.3	
741	AL 25	Q	43	28	8	58	48	34	89	89	48	26
		HP	0.1	0.2	0.3	0.5	0.6	0.7	1.1	1.1	1.4	1.6
744	AL 40	Q	137	112	76	177	158	132				
		HP	0.6	0.7	0.8	1.2	1.3	1.4				
745	AL 50	Q	205	176	140							
		HP	1.1	1.3	1.5							