



## Dual Range Metering Pump

- Wall mounted DLX
- Foot mounted DLXB
- Corrosion resistant plastic housing housing NEMA 4X (IP65)
- Manual bleed built into pump head (*standard*)
- 110 Volt or 220 Volt (12 or 24 VDC special order)
- Self Priming



DLXB pictured



Compact, robust manual pump with dual range 0-100% and 0-20%

Simply set the desired flowrate on the manual dial and turn it on.



Hoogeindsestraat 5  
 NL - 5447 PD Rijkevoort  
 Nederland  
 T : +31 (0) 485 - 371318  
 F : +31 (0) 485 - 371918  
 info@pompentechniek.nl  
 www.pompentechniek.nl

Manual stroke adjustment option is available on DLXB model only. (*special order*)

### Technical

- Pump head.....PP (polypropylene)
- Diaphragm.....PTFE
- Lip Valves.....Viton
- Injection Valve.....PP-viton
- Weight.....5-6 lbs (2.3-2.8 kg)
- Dimensions:
  - DLX..... 8.3 H x 5 W x 5.9 D
  - DLXB..... 8.7 H x 5 W x 7.6 D
  - with optional stroke adj.....8.7 H x 5 W x 8.5 D

### Accessories Supplied with the unit

- 6ft PVC transparent suction hose, 1/4"
- 6ft Polyethylene (PE) discharge hose, 1/4"
- 6ft PVC transparent bleed discharge hose, 1/4"
- 1 injection valve
- 1 filter/foot valve

### Ordering Information

ie DLX-MA/AD 0507 (110)

	Size	Voltage	gal/hr	PSI(max)	l/hr	Bar(max)
DLX-MA/AD DLXB-MA/AD	01-15	(110 or 220)	0.26	225	1	15
	02-20	(110 or 220)	0.52	290	2	20
	05-07	(110 or 220)	1.30	101	5	7
	05-12	(110 or 220)	1.30	130	5	12
	08-10	(110 or 220)	2.08	101	8	10
	15-04	(110 or 220)	3.96	58	15	4