

Kripsol KRF, KRB

Technische Specificaties

DESCRIPCION

BOMBAS PARA PISCINAS PUBLICAS

Bombas centrifugas KRIPSOL, serie KRIPTON normalizadas monobloc, conexión por brida DIN 2502, PN 16. Ø 100mm. Incorpora prefiltro con tapa mediante tres palomillas.

Modelos KRF: Cuerpo y prefiltro en fundición GG-22. **Turbinas en bronce.**

Modelo KRB: Cuerpo, turbina y prefiltro en bronce libre de zinc especial para agua de mar.

Motor clase F, 50Hz, protección IP55, 2.850 r.p.m.

Unidades disponibles a 60 Hz. Consultar.

DESCRIPTION

SWIMMING POOL PUMPS FOR COMMERCIAL POOLS

KRIPSOL centrifugal pumps KRIPTON series monobloc standardized flange connection DIN 2502, PN 16. Ø 100mm. Including prefILTER with closing of the lid by three hinged cover screws.

KRF models: Pump casing and prefILTER in cast iron GG-22.

Impeller in bronze.

KRB model: Pump casing, impeller and prefILTER in zinc free bronze.

Special for sea water. Motor: Protection IP 55, class F, 50 Hz, 2.850 r.p.m.

60 Hz. pumps available. Ask.

SERIE KRIPTON. MODELO KRF. BOMBA EN FUNDICION Y TURBINA EN BRONCE KRIPTON SERIES. KRF MODEL. PUMP IN CAST IRON AND IMPELLER IN BRONZE



MODELOS KRF
KRF MODELS

MODELO / MODEL TRIFÁSICA THREE-PHASE (1)	P2* HP	P1* KW	MOTOR MEC.	CAUDAL* l/h. FLOW*	PESO kg. WEIGHT	VOLUM. m³ VOLUME	UDS. Caja / Box QTY.
KRF 560 T1.B	5,50	4,9	112	71.300	117	0,122	1
KRF 560 T2.B	5,50	4,9	112	71.300	117	0,122	1
KRF 760 T1.B	7,50	7,0	112	97.000	122	0,122	1
KRF 760 T2.B	7,50	7,0	112	97.000	122	0,122	1
KRF1010 T1.B	10,00	8,7	132	109.000	124	0,122	1
KRF1010 T2.B	10,00	8,7	132	109.000	124	0,122	1
KRF1260 T1.B	12,50	10,7	132	135.000	144	0,122	1
KRF1260 T2.B	12,50	10,7	132	135.000	144	0,122	1
KRF1510 T2.B	15,00	13,3	132	147.000	150	0,122	1

*CAUDAL: En litros / hora a 14 m.c.a.

*FLOW: In liters / hour at 14 meters head.

DISPONIBLE HASTA FINAL DE STOCK.TILL THE STOCK IS FINISHED

SERIE KRIPTON. MODELO KRB. BOMBA Y TURBINA EN BRONCE.
KRIPTON SERIES. KRB MODEL. PUMP AND IMPELLER IN BRONZE

MODELO / MODEL
TRIFÁSICA
THREE-PHASE
(1)

	P2* HP	P1* KW	MOTOR MEC.	CAUDAL* l/h. FLOW*	PESO kg. WEIGHT	VOLUM. m³ VOLUME	UDS. Caja / Box QTY.
KRB 550 T1.B	5,50	4,9	112	71.300	128	0,122	1
KRB 550 T2.B	5,50	4,9	112	71.300	128	0,122	1
KRB 750 T1.B	7,50	7,0	112	97.000	133	0,122	1
KRB 750 T2.B	7,50	7,0	112	97.000	133	0,122	1
KRB1000 T1.B	10,00	8,7	132	109.000	135	0,122	1
KRB1000 T2.B	10,00	8,7	132	109.000	135	0,122	1
KRB1250 T1.B	12,50	10,7	132	135.000	157	0,122	1
KRB1250 T2.B	12,50	10,7	132	135.000	157	0,122	1
KRB1500 T2.B	15,00	13,3	132	147.000	163	0,122	1



MODELO KRB
KRB MODELS

*CAUDAL: En litros / hora a 14 m.c.a. *FLOW: In liters / hour at 14 meters head.

(1) FASES / PHASE

M- 230 Volt.

T1- 230/400 Volt.

T2- 400/700 Volt.

*POTENCIA / POWER

P1: Potencia absorbida / Power input

P2: Potencia nominal / power output